



WORLDWIDE ELECTRIC MOTOR DATA SHEET

PEWWE1-12-145T



HORSEPOWER	1		
RPM / POLES	1200 / 6		
VOLTAGE / PHASE	230 / 460 V / 3		
FRAME	145T		
ENCLOSURE / DEGREE OF PROTECTION	TEFC / IP55		
FREQUENCY	60 HZ Suitable For 50 HZ Operation With 1.0 SF		
FULL LOAD SPEED	1160 RPM		
SERVICE FACTOR	1.25		
INSULATION CLASS	F		
FULL LOAD AMPS; 230 / 460	3.49 / 1.75 A (Usable On 208V At 3.86 A)		
LOCKED ROTOR AMPS (STARTING); 230 / 460	30 / 15 A		
NO LOAD CURRENT	2.5 / 1.25 A		
NEMA CODE LETTER	N		
EFFICIENCY / POWER FACTOR	<u>LOAD</u>	<u>EFF.</u>	<u>P.F.</u>
	100 %	82.5%	0.65
	75 %	82.0%	0.58
	50 %	78.3%	0.45
DUTY CYCLE	S1 / Continuous		
TORQUE	<u>FULL LOAD</u>	<u>LRT</u>	<u>BDT</u>
	4.53 lb.ft.	170%	280%
SLIP	3.33 %		
NEMA DESIGN	B		
MOMENT OF INERTIA	0.113 lb.ft. ²		
MAX. TIME LOCKED ROTOR (Hot)	13 Seconds		
SOUND PRESSURE LEVEL	55 dB (A)		
MAX. AMBIENT TEMPERATURE	40° C		
MAX. ELEVATION	3300 Ft.		
TEMPERATURE RISE (At Full Load)	80° C		
DE BEARING	6205ZZ C3		
ODE BEARING	6205ZZ C3		
REGREASING INT. - DE BEARING	---		
REGREASING INT. - ODE BEARING	---		
GREASE TYPE	SKF LGHP 2		
MOUNTING	F1 (F2 Suitable)		
ROTATION	Bi-Directional		
SHAFT MATERIAL	1045 Carbon Steel		
INVERTER RATING	10:1 CT / 20:1 VT PWM Type		
CONNECTION DIAGRAM	230 / 460 V - 9 Lead Y		
AREA CLASSIFICATION	Class I, Division 2, Groups A, B, C, D		
APPROXIMATE WEIGHT	53 lbs.		




CC006A





WORLDWIDE ELECTRIC MOTOR DRAWING

PEWWE-145T



DIMENSIONS - INCHES

MOUNTING					A	B	C	D	G	J	P	L	AB
E	2F1	2F2	H	BA									
2.75	4	5	0.34	2.25	7	6.6	13.5	3.5	0.43	1	7.8	7.6	6.7

KEY		KEYSET	SHAFT		TERMINAL BOX				
S	ES	R	N-W	U	AA	XB	XC	XD	XE
0.188	1.41	0.771	2.25	0.875	0.75	1.6	4.6	4.1	4.45

PERFORMANCE CURVES

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net





Premium Efficiency Motor:

PEWWE1-12-145T

Document Generated: 25-Jun-2020
Document ID:

Customer:

Motor Type	PEWWE		FL Speed	1160	
Output Rating (HP)	1		LRT (%FLT)	170	460 volt FLA 1.75
Full Load Torque	4.53	lb.ft	BDT (%FLT)	280	230 volt FLA 3.49A
Rotor Wk ²	0.113	lb-ft ²			



NAMEPLATE / WIRING

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Premium Efficiency Motor:

PEWWE1-12-145T

Document Generated: 21-Aug-2019
Document ID:

Customer:

SAMPLE NAMEPLATE DATA

		PREMIUM EFFICIENCY 3-PHASE INDUCTION MOTOR		CC006A ISO9001	259277
Model	PEWWE1-12-145T	Ser No.	ZP		
HP	1	S.F.	1.25	Type	Encl TEFC IP55
Frame	145T	P.F.	0.68	Ins Cl	F
Voltage	230/460	Hz	60 Hz	Design	B
Amps	3.49A / 1.75A	RPM	1160	Code	N
Nom. Eff.	FL 82.5 %	3/4 82.2 %	230/460V		Date
Usable on 208V network at 4 Amps 1.0SF		Class I DIV. 2 Groups A B C D		Amb.40°C	T3C(160°C)
10:1 CT 20:1 VT PWM VFD 1.0SF		Class I Zone 2 IIC		Amb.55°C	T3A(180°C)
50Hz 1 HP 200/400 V V 4.37 / 2.18 A 955 rpm S.F1.0					

Low Voltage

High Voltage

