DATA SHEET

Premium Efficiency Motor: **PEWWE250-18-505UZ** **60 Hz**

WorldWide Electric Corporation
1 (800) 808-2131
Worldwideelectric.net

Document Generated:	31-Jul-2023
Document ID:	

Customer:

MOTOR INFORMATION

HP	250
RPM	1800
Phase	3
Frequency	60 Hz
Voltage	460 V
Frame Size	505UZ
Enclosure	TEFC
Degree of Protection	IP55
Service Factor	1.15
Poles	4
Full Load Speed	1790
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	G
Duty Cycle	S1 / Continuous
Slip	0.56%
NEMA Design	B
Moment of Inertia	73.6 lb.ft.^2
Locked Rotor Time (Hot)	17 seconds
Sound Pressure Level	85 dB(A)
Number of Starts	2 Cold/ 1 Hot
Max Ambient Temperature	40°C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bi-Directional
Area of Classification	Class 1 Division 2 Groups A,B,C,D T3(200°C)
Inverter Rating	10:1 CT / 20:1 VT PWM Type
Standard	NEMA MG-1
Approvals	CSA-US, CE

ADDITIONAL DATA

F2 Suitable	No
Shaft Material	4140 Carbon Steel
Connection Diagram	460 V - 6 Lead Δ
Approximate Weight	2360 lbs.

EFFICIENCY/POWER FACTOR

LOAD	EFF	P. F.
100%	96.2 %	0.87
75%	96.2 %	0.84
50%	95.8 %	0.75

TORQUE

FULL LOAD	LRT	BDT
1027 lb.ft.	200 %	250 %

AMPERAGE INFORMATION

	230V	460V
Full Load Amps	--A	280A
Locked Rotor Amps	--A	1825A
No Load Current	--A	93A
Usable at 208V	--A	

BEARING INFORMATION

DE Bearing	NU322 C3
ODE Bearing	6319 C3
Grease Type	SKF LGHP 2
DE Regreasing Interval	1300 Hours
ODE Regreasing Interval	2000 Hours

This document is the property of WorldWide Electric Corporation and may not be reproduced without express authorization

MOTOR DRAWING

Premium Efficiency Motor: **PEWWE250-18-505UZ**

WorldWide Electric Corporation
1 (800) 808-2131
Worldwideelectric.net



DIMENSION - INCHES

MOUNTING					A	B	C	D	G	J	P	O	T	AB
E	2F1	2F	H	BA										
10	16	18	0.94	8.5	24.72	26	55	12.5	1.87	4.72	25	25.3	4.25	21

SHAFT & KEY				
S	ES	R	N-W	U
1	10	3.309	11.625	3.875

TERMINAL BOX				
AA	XB	XC	XD	XF
2X3	5	13.8	11.8	--

This document is the property of WorldWide Electric Corporation and may not be reproduced without express authorization

PERFORMANCE CURVES

Premium Efficiency Motor: **PEWWE250-18-505UZ**

WorldWide Electric Corporation
1 (800) 808-2131
Worldwideelectric.net

Document Generated:	31-Jul-2023
Document ID:	

Customer:

Motor Type	PEWWE							
Output Rating (HP)	250		FL Speed	1790				
Full Load Torque	1027	lb.ft	LRT (%FLT)	200	460 volt FLA	280	A	
Rotor Wk^2	73.6	lb-ft^2	BDT (%FLT)	250	230 volt FLA	--	A	





This document is the property of WorldWide Electric Corporation and may not be reproduced without express authorization.

NAMEPLATE / WIRING

Premium Efficiency Motor: **PEWWE250-18-505UZ**

WorldWide Electric Corporation
1 (800) 808-2131
Worldwideelectric.net

Document Generated: 31-Jul-2023 Document ID:	Customer:

SAMPLE NAMEPLATE DATA

WORLDWIDE

NEMA Premium®

3-PHASE INDUCTION MOTOR

259277 C SP® US CE

Model				Ser No.			
HP		S.F.		IP		Encl	
Frame		P.F.		Code		Type	
Voltage		Hz		Ins Cl		Rating	°C Amb Cont
Amps		RPM		Design		Date	
Nom.Eff.	FL % 3/4 % V			10:1 CT 20:1 VT PWM VFD 1.0SF			
Class Ⅰ DIV. 2 Groups A B C D				Amb.40℃			
DE Brng ODE Brng				Grease type: LGHP 2 (compatible with polyrex)			

Connection



LEADGO®

WorldWide Electric Corporation

Model	PEWWE250-18-505UZ						
HP	250	S.F.	1.15	IP	IP55	Encl	TEFC
Frame	505UZ	P.F.	0.87	Code	G	Type	
Voltage	460 V	Hz	60 Hz	Ins Cl	F	Ambient	40°C
Amps	280	RPM	1790	Design	B	DE Brng	NU322 C3
Nom.Eff.	FL 96.2% 3/4 96.2%					ODE Brng	6319 C3
Class 1 Division 2 Groups A,B,C,D T3(200°C)						Grease type:	SKF LGHP 2

50Hz	--	HP	--	--	A	-- rpm

This document is the property of WorldWide Electric Corporation and may not be reproduced without express authorization